



all solutions in one partner®

SCHEDA TECNICA - CODICE NF57000-032JY



VITE AUTOFILETTANTE FOSFATATA NERA - DOPPIO FILETTO-DOPPIA PUNTA - TOP QUALITY - JY®

Vite fosfatata da cartongesso per fissaggio lastre-lamiera con eccezionale tempo di perforazione medio per la vite 3.5x25 di 0,375 sec.

Le misure 3.5x25 e 3.5x35 possono essere fornite anche in buste o in barattoli da 1000 pz o rispettivamente da 7000 e 5000 pz.

Inoltre per i codici NF57002, NF57003 e NF57004 è possibile fornire la confezione personalizzata con il nome ed il logo del cliente.

La stessa vite nastrata crea il codice NF59.



MATERIALI

Acciaio 1018

Resistenza al Salt Spray Test: 48h

AVVERTENZE

- L'utilizzazione e il montaggio del prodotto è esclusivamente riservato al personale esperto.
- Il prodotto è monouso nel senso che le caratteristiche di durata stabilità e tenuta sono garantite per una singola applicazione e in nessun caso può essere riutilizzato in altre applicazioni.



all solutions in one partner®

SCHEDA TECNICA - CODICE NF5700-032JY



INFORMAZIONI TECNICHE:

CODICE	DIAMETRO/ LUNGHEZZA (mm)	CONFEZIONE - PZ	IMBALLO - PZ	BANCALE - PZ
NF57032JY	Ø 3,0 x 25	1.000	16.000	576.000
NF57001	Ø 3,5 x 19	500	16.000	384.000
NF57002JY	Ø 3,5 x 25	1.000	16.000	384.000
NF57000	Ø 3,5 x 30	1.000	12.000	384.000
NF57003JY	Ø 3,5 x 35	1.000	12.000	288.000
NF57004JY	Ø 3,5 x 45	1.000	8.000	192.000
NF57005JY	Ø 3,5 x 55	1.000	6.000	144.000
NF57006	Ø 4,2 x 70	500	4.000	96.000
NF57007	Ø 4,2 x 80	500	4.000	96.000
NF57008	Ø 4,8 x 90	250	3.000	72.000
NF57009	Ø 4,8 x 100	250	2.000	48.000
NF57010	Ø 4,8 x 110	250	2.000	48.000
NF57011	Ø 4,8 x 120	250	2.000	48.000
NF57012	Ø 4,8 x 130	250	2.000	48.000
NF57013	Ø 4,8 x 140	250	2.000	48.000
NF57014	Ø 4,8 x 150	100	1.200	28.800
NF57015	Ø 4,8 x 160	100	1.200	28.800

CONFEZIONE RIDOTTA:

CODICE	DIAMETRO/ LUNGHEZZA (mm)	CONFEZIONE - PZ	IMBALLO - PZ	BANCALE - PZ
NF57016	Ø 3,5x25	200	9.600	230.400
NF57017	Ø 3,5x35	200	9.600	230.400
NF57018	Ø 3,5x45	200	4.800	115.200
NF57019	Ø 3,5x55	200	4.800	115.200



all solutions in one partner®

SCHEMA TECNICA - CODICE NF5700-032JY



VALORI DI ESTRAZIONE:

CODICE	RESISTENZA ALLO STRAPPO SU LAMIERA 6/10		RESISTENZA GARANTITA ALLO STRAPPO SU LAMIERA 6/10	
	[kgf]	[kN]	[kgf]	[kN]
NF57032JY	208	2,08	104	1,04
NF57001	208	2,08	104	1,04
NF57002JY	208	2,08	104	1,04
NF57000	208	2,08	104	1,04
NF57003JY	208	2,08	104	1,04
NF57004JY	208	2,08	104	1,04
NF57005JY	208	2,08	104	1,04
NF57006	208	2,08	104	1,04
NF57007	208	2,08	104	1,04
NF57008	208	2,08	104	1,04
NF57009	208	2,08	104	1,04
NF57010	208	2,08	104	1,04
NF57011	208	2,08	104	1,04
NF57012	208	2,08	104	1,04
NF57013	208	2,08	104	1,04
NF57014	208	2,08	104	1,04
NF57015	208	2,08	104	1,04
NF57016	208	2,08	104	1,04
NF57017	208	2,08	104	1,04
NF57018	208	2,08	104	1,04
NF57019	208	2,08	104	1,04

Coefficiente di sicurezza adottato: 2



all solutions in one partner®

SCHEMA TECNICA - CODICE NF5700-032JY



VALORI DI RESISTENZA A TAGLIO:

CODICE	RESISTENZA A TAGLIO SU LAMIERA 6/10		RESISTENZA GARANTITA A TAGLIO SU LAMIERA 6/10	
	[kgf]	[kN]	[kgf]	[kN]
NF57032JY	240	2,40	120	1,20
NF57001	240	2,40	120	1,20
NF57002JY	240	2,40	120	1,20
NF57000	240	2,40	120	1,20
NF57003JY	240	2,40	120	1,20
NF57004JY	254	2,54	127	1,27
NF57005JY	264	2,64	132	1,32
NF57006	260	2,60	130	1,30
NF57007	260	2,60	130	1,30
NF57008	260	2,60	130	1,30
NF57009	264	2,64	132	1,32
NF57010	240	2,40	120	1,20
NF57011	240	2,40	120	1,20
NF57012	240	2,40	120	1,20
NF57013	240	2,40	120	1,20
NF57014	240	2,40	120	1,20
NF57015	240	2,40	120	1,20
NF57016	240	2,40	120	1,20
NF57017	240	2,40	120	1,20
NF57018	254	2,54	127	1,27
NF57019	264	2,64	132	1,32

Coefficiente di sicurezza adottato: 2



all solutions in one partner®

DATA SHEET - CODE NF5700-032JY



BLACK PHOSPHATED SELF-TAPPING SCREW - DOUBLE THREAD/DOUBLE TIP - TOP QUALITY - JY®

Phosphated plasterboard screw for sheetlaminat fixing with an outstanding average drilling time for the 3.5x25 screw of 0.375 sec.

The 3.5x25 and 3.5x35 sizes can also be supplied in bags or in cans of 1000 pcs. or 7000 and 5000 pcs. Respectively.

In addition, for codes NF57002, NF57003 and NF57004, customised packaging with the customer's name and logo can be supplied.

The same taped screw creates the code NF59.



MATERIALS

1018 steel

Resistance of Salt Spray Test: 48h

WARNINGS

- The use and assembly of the product is exclusively reserved for skilled staff.
- The product is single-use. That means its characteristics of durability, stability and tightness are guaranteed for a single application and in no case it may be reuse in other applications.



all solutions in one partner®

DATA SHEET - CODE NF5700-032JY



TECHNICAL INFORMATION:

CODE	DIAMETER/LENGTH (mm)	BOX - PCS	PACKAGING - PCS	PALLET - PCS
NF57032JY	Ø 3,0 x 25	1.000	16.000	576.000
NF57001	Ø 3,5 x 19	500	16.000	384.000
NF57002JY	Ø 3,5 x 25	1.000	16.000	384.000
NF57000	Ø 3,5 x 30	1.000	12.000	384.000
NF57003JY	Ø 3,5 x 35	1.000	12.000	288.000
NF57004JY	Ø 3,5 x 45	1.000	8.000	192.000
NF57005JY	Ø 3,5 x 55	1.000	6.000	144.000
NF57006	Ø 4,2 x 70	500	4.000	96.000
NF57007	Ø 4,2 x 80	500	4.000	96.000
NF57008	Ø 4,8 x 90	250	3.000	72.000
NF57009	Ø 4,8 x 100	250	2.000	48.000
NF57010	Ø 4,8 x 110	250	2.000	48.000
NF57011	Ø 4,8 x 120	250	2.000	48.000
NF57012	Ø 4,8 x 130	250	2.000	48.000
NF57013	Ø 4,8 x 140	250	2.000	48.000
NF57014	Ø 4,8 x 150	100	1.200	28.800
NF57015	Ø 4,8 x 160	100	1.200	28.800

REDUCED PACKAGING:

CODE	DIAMETER/LENGTH (mm)	BOX - PCS	PACKAGING - PCS	PALLET - PCS
NF57016	Ø 3,5x25	200	9.600	230.400
NF57017	Ø 3,5x35	200	9.600	230.400
NF57018	Ø 3,5x45	200	4.800	115.200
NF57019	Ø 3,5x55	200	4.800	115.200



all solutions in one partner®

DATA SHEET - CODE NF5700-032JY



EXTRACTION VALUE:

CODE	TEAR RESISTANCE ON SHEET METAL 6/10		GUARANTEED RESISTANCE TO TEAR ON SHEET METAL 6/10	
	[kgf]	[kN]	[kgf]	[kN]
NF57032JY	208	2,08	104	1,04
NF57001	208	2,08	104	1,04
NF57002JY	208	2,08	104	1,04
NF57000	208	2,08	104	1,04
NF57003JY	208	2,08	104	1,04
NF57004JY	208	2,08	104	1,04
NF57005JY	208	2,08	104	1,04
NF57006	208	2,08	104	1,04
NF57007	208	2,08	104	1,04
NF57008	208	2,08	104	1,04
NF57009	208	2,08	104	1,04
NF57010	208	2,08	104	1,04
NF57011	208	2,08	104	1,04
NF57012	208	2,08	104	1,04
NF57013	208	2,08	104	1,04
NF57014	208	2,08	104	1,04
NF57015	208	2,08	104	1,04
NF57016	208	2,08	104	1,04
NF57017	208	2,08	104	1,04
NF57018	208	2,08	104	1,04
NF57019	208	2,08	104	1,04

Safety factor: 2



all solutions in one partner®

DATA SHEET - CODE NF5700-032JY



VALUE OF SHEAR RESISTANCE:

CODE	SHEAR RESISTANCE ON SHEET METAL 6/10		GUARANTEED SHEAR RESISTANCE ON SHEET METAL 6/10	
	[kgf]	[kN]	[kgf]	[kN]
NF57032JY	240	2,40	120	1,20
NF57001	240	2,40	120	1,20
NF57002JY	240	2,40	120	1,20
NF57000	240	2,40	120	1,20
NF57003JY	240	2,40	120	1,20
NF57004JY	254	2,54	127	1,27
NF57005JY	264	2,64	132	1,32
NF57006	260	2,60	130	1,30
NF57007	260	2,60	130	1,30
NF57008	260	2,60	130	1,30
NF57009	264	2,64	132	1,32
NF57010	240	2,40	120	1,20
NF57011	240	2,40	120	1,20
NF57012	240	2,40	120	1,20
NF57013	240	2,40	120	1,20
NF57014	240	2,40	120	1,20
NF57015	240	2,40	120	1,20
NF57016	240	2,40	120	1,20
NF57017	240	2,40	120	1,20
NF57018	254	2,54	127	1,27
NF57019	264	2,64	132	1,32

Safety factor: 2